

A7 Automatic Dispenser



- ➔ 1L/min High Efficiency
Suitable for Batch
Dispensing
- ➔ 1/2000Y High Accuracy
Suitable for Sample
Paint Dispensing
- ➔ 100% Recirculation
Suitable for Z-VOC
Colorant

● Electric can table

SANTINT • CHINA

Add: Feilong Road, Xingyang,
Zhengzhou, China
Email: info@santint.com

SANTINT • HOLLAND

Add: Lageweg 35 - J, 2222 AG
Katwijk The Netherlands
Email: sales@santint-europe.com

SANTINT • POLAND

Add:43 Szyszkowa Street,
02-285 Warsaw, Poland
Email:albert@santintpoland.com

SANTINT • U.S.A

Add: 2000 Bloomingdale Road,
Suite 205, Glendale Heights,
IL 60139, U.S.A
Email: info@santintusa.com

SANTINT • BRAZIL

Add: Av.Rosa Kasinski,
1109, G29 Capuava,Mauá,
SP - Brasil CEP 09380-128
Email: marcos@santint.com

SANTINT • INDIA

Add: H.No.692, Gala No.04, Print
World Industrial Complex,
Bhatale, Vehele Village, Opposite
Balaji Compound, Bhiwandi,
Maharashtra - 421302
Email: nick@santint.com

A7 Main Features >>>



1 Preferred Option for Medium/High Volume Locations

High efficiency piston pump shortens tinting time.




2 Suitable for Sample Paint Dispensing

High accuracy Small pump & small nozzle, suitable for sample paint dispensing



3 Suitable for Z-VOC Colorant

100% recirculation technology. Timed recirculation makes the colorant noncondensing and prevents the nozzle from dryness and blockage & colorant from deterioration.



4 LCD Timely Displays Machine Status

5 Weight Feedback Function Optional

Electronic scale real-time feedbacks dispensing amount. Accurate compensation can be achieved according to feedback value. It applies to industrial paint, ink, automotive paint, etc.

■ Canister configuration

16 canisters: 4 x 12L+12 x 6L
24 canisters: 18 x 6L+6 x 2.3L
32 canisters: 8 x 6L+24 x 2.3L
36 canisters: 9 x 6L+27 x 2.3L

- Pump configuration: sequential piston pump
- Single Pump Standard Efficiency: 1L/min
- Minimum Shot: 1/2000Y(0.015ml) *It depends on the product property

- Applicable can: diameter≤490mm, height≤420mm
- Can table: electrical
- Mixing Speed: 20-25r/min

- Machine Dimension(W x D x H): 1100 x 1270 x 1325mm
- Packing Dimension(W x D x H): 1150 x 1400 x 1400mm
- 8 pcs/20GP 16 pcs/40GP

- Net Weight: 350kg
- Gross Weight: 450kg

- Power Supply: 220V/110V 50Hz/60Hz
- Rated Power: 450W



Technical Parameters

